



FEATURES

- 5 selectable positions of fluid pan and tilt drag + 0.
- 16 position CB Plus™ counterbalance system.
- Perfect for payloads to 1-19kg (2.2-41.8lbs).
- Quick action column lock.
- Smooth 350mm (13.8") stroke.
- Independent 125mm dolly wheel brake system.
- Sturdy adjustable cable guards.
- Steering wheel diameter 294mm (11.6").
- Dolly tracking width 920mm (36.2").

Light Weight & Portable Pedestal

Payload Range	1.0-19.0kg (2.2-41.8lbs)
Weight	18.0kg (39.7lbs)
Height Range	1062-1412mm (41.8-55.6")
Mounting Base	Ø100mm (3.9") ball levelling
Column In-Shot Stroke	350mm (13.8")
Steering Wheel Diameter	Ø294mm (11.6")
Tracking Width	1072mm (42.2")
Wheel Diameter	Ø294mm (11.6")

Components

1072	Arrowx 3 fluid head
696	2 x Pan handle - telescopic with clamp
1960	Combo pedestal



Quality
ISO 9001

SAI GLOBAL
Australia only

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 2),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us