



FEATURES

- Compact and portable with carry handle.
- Supports payloads up to 200 kg (440.1 lbs).
- Independent dolly wheel axle brake system eliminates wheel tyre indents.
- Multiple wheel positions for linear or radius dolly tracking.
- 125mm (4.9") dual ball bearing wheels for quick swivel-turn action.
- Dolly tracking width 970mm (38.2").
- Sturdy adjustable cable guards.
- Quick fold away design.
- Suited for Miller HD and Sprinter II Tripods

Solid Studio Support For HD and Sprinter Tripods

SPECIFICATIONS

Weight:	9.2 kg (20.2 lbs)
Payload capacity:	200 kg (440.9 lbs)
Tracking width:	970 mm (38.2")
Minimum width:	840 mm (33.1")
Footprint diameter:	1120 mm (44.1")
Wheel diameter:	125 mm (4.9")
Transport length:	760 mm (29.9")
Height above ground:	200 mm (7.9")
Wheel lock:	Axle lock type

OPTIONAL ACCESSORIES

3294 Weight bag 5.6 kg (12.3 lbs)



Quality
ISO 9001

SAI GLOBAL

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 15 & 16),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us