



FEATURES

- Compact and portable with carry handle.
- Supports payloads up to 200 kg (440.1 lbs).
- Independent dolly wheel axle brake system eliminates wheel tyre indents.
- Multiple wheel positions for linear or radius dolly tracking.
- 125mm (4.9") dual ball bearing wheels for quick swivel-turn action.
- Dolly tracking width 970mm (38.2").
- Sturdy adjustable cable guards.
- Quick fold away design.
- Suited for HD Studio Tripod (3354)

Solid Studio Support For HD Studio Tripod

SPECIFICATIONS

Weight:	9.2 kg (20.2 lbs)
Payload capacity:	200 kg (440.9 lbs)
Tracking width:	970 mm (38.2")
Minimum width:	840 mm (33.1")
Footprint diameter:	1120 mm (44.1")
Wheel diameter:	125 mm (4.9")
Transport length:	760 mm (29.9")
Height above ground:	200 mm (7.9")
Wheel lock:	Axle lock type

OPTIONAL ACCESSORIES

3294 Weight bag 5.6 kg (12.3 lbs)



CAUTION!



When used with Skyline 90 fluid head.

To maintain stability in system do not exceed 30 degrees of tilt and use 3 x #3294 weight bag on dolly.



AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 15 & 16),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us