



FEATURES

- Mitchell base for flat mounting.
- One stage alloy rotary lock leg extension for heavy duty clamping.
- Heavy duty clear anodised alloy tubing.
- Cast alloy brackets for rigid geometry.
- Suited for HD Dolly and all Mitchell base heads.
- 3 year warranty.

* Pictured with HD Dolly w/ Cable Guards #3225 (sold separately).

Mitchell Base Tripod for HD Dolly

SPECIFICATIONS

Weight:	8.4 kg (18.5 lbs)
Payload capacity:	140.0 kg (308.7 lbs)
Height range:	700 - 1100 mm (27.6 - 43.3")**
Mounting base:	Mitchell base
Transport length:	680 mm (26.8")
Leg extension:	1 stage
Lock type:	Rotary lock
Leg material:	Alloy
Warranty:	3 Years

OPTIONAL ACCESSORIES

3225	HD Dolly w/ Cable Guards
------	--------------------------

** Includes Studio Dolly height



Quality
ISO 9001

SAI GLOBAL

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 15 & 16),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us