



#2111**



#2122*

FEATURES

- Available in various mounting bases (100, 150, MB).
- Available in ground spreader or mid-level spreader versions.
- One stage alloy rotary lock leg extension for heavy duty clamping.
- Heavy duty all black anodised alloy tubing.
- Robust glass-filled polymer brackets.
- Integrated stainless steel foot spikes.
- Integrated transport clips to pack system down securely.
- 3 year warranty.

*Pictured with #993 Mid-Level Spreader and #478 Feet (opt.)

**Pictured with #2130 HDC Ground Spreader (opt.)

Tall HD Cine Tripods with Rotary Locking

SPECIFICATIONS

Weight:

- 6.0 kg (13.2 lbs) - 100mm
- 6.2 kg (13.7 lbs) - 150mm
- 6.4 kg (14.1 lbs) - MB

Ground spreader version

Height range:

- 845-1690mm (33.3-66.5") - 100mm
- 876-1754mm (34.5-69.1") - 150mm
- 886-1764mm (34.9-69.5") - MB

Mid-level spreader version

Height range:

- 890-1755mm (35.0-69.1") - 100mm
- 915-1765mm (46.0-69.5") - 150mm
- 925-1775mm (36.4-70.0") - MB

OPTIONAL ACCESSORIES

993	Mid-Level Spreader
478	HD Feet (set of 3)
2130	HDC Ground Spreader



Quality
ISO 9001
SAI GLOBAL

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 15 & 16),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us

HDC TRIPOD SPECIFICATIONS

#	2109	2110	2111	2114	2115	2116	2120	2121	2122
Bowl	MB			150mm			100mm		
Height	Short	Std	Tall	Short	Std	Tall	Short	Std	Tall
Height range	365-910mm (14.4-35.8")	800-1550mm (31.5-61.0")	925-1775mm (36.4-70.0")	355-900mm (14.0-35.0")	790-1540mm (31.1-60.6")	915-1765mm (46.0-69.5")	315-895mm (12.4-35.2")	770-1537mm (30.3-60.1")	890-1755mm (35.0-69.1")
Travel length	610mm (24.0")	916mm (36.1")	1010mm (39.8")	600mm (23.6")	906mm (35.7")	1000mm (39.4")	600mm (23.6")	906mm (35.7")	1000mm (39.4")
Weight	4.8kg (10.6lbs)	5.9kg (13.2lbs)	6.4kg (14.1lbs)	4.5kg (9.9lbs)	5.6kg (12.4lbs)	6.2kg (13.7lbs)	4.3kg (9.5lbs)	5.4kg (11.9lbs)	6.0kg (13.2lbs)
Spread-er (opt.)	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478	993 + 478

#	2109G	2110G	2111G	2114G	2115G	2116G	2120G	2121G	2122G
Bowl	MB			150mm			100mm		
Height	Short	Std	Tall	Short	Std	Tall	Short	Std	Tall
Height range	415-900mm (16.4-35.4")	737-1549mm (29.0-61.0")	886-1764mm (34.9-69.5")	405-890mm (16.0-35.0")	727-1539mm (28.2-60.6")	876-1754mm (34.5-69.1")	370-900mm (14.6-35.4")	710-1539mm (28.0-60.6")	845-1690mm (33.3-66.5")
Travel length	640mm (25.2")	946mm (37.2")	1040mm (41.0")	630mm (24.8")	936mm (36.9")	1030mm (40.6")	630mm (24.8")	936mm (36.9")	1030mm (40.6")
Weight	4.8kg (10.6lbs)	5.9kg (13.2lbs)	6.4kg (14.1lbs)	4.5kg (9.9lbs)	5.6kg (12.4lbs)	6.2kg (13.7lbs)	4.3kg (9.5lbs)	5.4kg (11.9lbs)	6.0kg (13.2lbs)
Spread-er (opt.)	2132	2130	2130	2132	2130	2130	2132	2130	2130


AUSTRALIA
 Miller Camera Support Equipment
 30 Hotham Parade
 Artarmon, Sydney, NSW 2064
 Australia
 Quality ISO 9001
 P +61 2 9439 6377 F +61 2 9438 2819
 sales@miller.com.au

EUROPE
 Miller Fluid Heads (Europe) Ltd.
 Unit 12A, Shepperton Business Park
 Govett Avenue, Shepperton
 Middlesex, TW17 8BA
 United Kingdom
 P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
 sales@millertripods-europe.com

USA
 Miller Camera Support LLC
 216 Little Falls Road (Unit 15 & 16),
 Cedar Grove, New Jersey 07009
 USA
 P +1 (973) 857 8300 F +1 (973) 857 8188
 sales@millertripods.us