



FEATURES

- 75mm alloy bowl.
- 2 stage fast toggle adjustment legs.
- Durable black anodised alloy tubing.
- Flip out transport clips.
- Suited for on ground spreader (411).
- Integrated stainless steel foot spikes.
- Stay flat rubber feet (optional).
- 3 year warranty.

*Pictured with On Ground Spreader (411)

Affordable, Light Weight Performer

SPECIFICATIONS

Weight:	3.0 kg (6.6 lbs)
Payload capacity:	25.0 kg (55.0 lbs)
Height range:	390 - 1560 mm (15.4 - 61.4")
Bowl diameter:	75 mm (3.9")
Transport length:	690 mm (27.2")
Footprint diameter:	910 - 1310 mm (31.8 - 51.6")
Leg extension:	2 stage
Lock type:	Toggle type
Leg material:	Alloy
Warranty:	3 Years

OPTIONAL ACCESSORIES

390	MD pro dolly
391	LW pro dolly
550	Rubber feet (set of 3)
411	On ground spreader
508	Above ground spreader
835	Above ground spreader
378	D75 - D100 tripod bowl adapter



Quality
ISO 9001

SAI GLOBAL
Australia only

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 2),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us