



FEATURES

- Compact and portable with carry handle for dolly.
- Wide height range 900 mm (35.4") up to 1250 mm (49.2").
- Simple and easy to setup and use.
- Air adjustable column system for quick payload balancing.
- Quick action column lock.
- Smooth 350 mm (13.8") stroke.
- Independent 125 mm (4.9") dolly wheel brake system.
- Sturdy adjustable cable guards.
- Steering wheel diameter 294 mm (11.6").
- Dolly tracking width 920 mm (36.2").
- Portable hand pump not included.

Light Weight & Portable Pedestal

SPECIFICATIONS

Weight Total:	11.6 kg (25.6 lbs)
Weight Dolly:	6.6 kg (14.6 lbs)
Weight Column:	5.0 kg (11.0 lbs)
Payload range (column):	30.0 kg (66.1 lbs)
Column in-shot stroke:	350 mm (13.8")
Min. height:	900 mm (35.4")
Max. height:	1250 mm (49.2")
Tracking width:	920 mm (36.2")
Footprint diameter:	1072 mm (42.2")
Steering wheel diameter:	294 mm (11.6")
Mounting base:	Bowl type
Bowl diameter:	Ø100 mm (3.9")
Wheel diameter:	Ø125 mm (4.9")
Transport width (pedestal):	294 mm (11.6")
Transport height (pedestal):	690 mm (27.1")
Transport length (dolly):	785 mm (30.9")

OPTIONAL ACCESSORIES

N/A

SPARES

N/A



Quality
ISO 9001

SAI GLOBAL
Australia only

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 2),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us