



FEATURES

- Affordable, Stable, Robust.
- 100mm ball levelling.
- Perfect for payloads to 0-12kg (26.4bs).
- 15+0 selectable counterbalance positions.
- Ergonomically located CB Plus™ switch.
- 5+0 selectable positions of fluid pan and tilt drag.
- 2-stage rapid leg lock extension.
- Lightweight carbon fibre legs.
- Comes with 2-stage tripod bag.
- 3 year warranty.

Affordable, stable and robust

SPECIFICATIONS

Payload Range	0-12kg (0-26.4lbs)
Weight	5.7kg (12.7lbs)
Height Range	395-1793mm (15.5-70.6")
Transport Length	942mm (37")
Counterbalance Positions	16 selectable positions (15+0)
Pan Tilt Drag	5 selectable fluid drag positions + 0
Pan Tilt Locks	Positive lock calliper brake system
Tilt Range	+90° / -75°
Pan Range	360°
Camera Platform	Quick release, side load camera plate
Sliding Range	60mm (2.4")
Mounting Base	Ø100mm (3.9") ball levelling
Height Above Bowl	150mm (6.0")
Illuminated Controls	Bubble level
Pan Handle	Fixed Length 390mm (15.4")
Temperature Range	-40° to +65°C (-40° to +150°F)
Leg Extension	2-stage telescopic
Lock Type	Concentric Rapid Lock & Q-lock
Leg Material	Carbon Fibre

COMPONENTS

1096	CX10 fluid head
2515	Solo-Q 100 2-stage tripod (carbon fibre)
679	Pan handle - fixed with clamp
1520	Solo-Q Shoulder strap (padded)
3514	Softcase 2-stage

*System weights do not include the weight of the bag



Quality
ISO 9001

SAI GLOBAL
Australia only

AUSTRALIA

Miller Camera Support Equipment
30 Hotham Parade
Artarmon, Sydney, NSW 2064
Australia

P +61 2 9439 6377 F +61 2 9438 2819
sales@miller.com.au

EUROPE

Miller Fluid Heads (Europe) Ltd.
Unit 12A, Shepperton Business Park
Govett Avenue, Shepperton
Middlesex, TW17 8BA
United Kingdom

P +44 (0) 1932 222 888 F +44 (0) 1932 222 211
sales@millertripods-europe.com

USA

Miller Camera Support LLC
216 Little Falls Road (Unit 2),
Cedar Grove, New Jersey 07009
USA

P +1 (973) 857 8300 F +1 (973) 857 8188
sales@millertripods.us